

TECHNICAL DATASHEET

PLASTIC PRIMER

PRODUCT DESCRIPTION

Quick drying, adhesion primer for car bumpers and all plastic surfaces. It has excellent adhesion and high resistance to sagging on vertical surfaces.

PRODUCT BENEFITS

- 1- Excellent adhesion to plastic substrates
- 2- Excellent filling properties
- 3- Quick drying
- 4- Long lasting elasticity
- 5- Good compatibility with all types of paints

RECOMMENDED USES

Ideal for use on all plastic car body parts to promote the adhesion of topcoats.



SURFACE PREPARATION

Pre-clean the surface with warm water and detergent, rinse sufficiently with clean water.

Untreated plastic part


Thoroughly abrade all surfaces in combination with water.

Use an abrasive pad on hard plastics. Rinse sufficiently with clean water after use.

Painted plastic part

Sanding should be carried out

For spot repair, sand the feather edge



TECHNICAL CHARACTERISTICS


Color: Clear

Density: 0.9 - 1 g/ cm³

Spreading rate: Average spreading of one container is about 20-25 m² / US quart



Thinning: No thinning required



Spraying Viscosity: 18 to 20 seconds ISO 4 cups @ 25⁰C




Number of spray coats: 1 or 2


Scratching test: Excellent



Drying time: at 25⁰C, 10-15 min



Recoating: Allow for a minimum of 20 minutes' flash-off time before recoating.



Hold approximately 12-18 cm from the panel and apply 1 even coat over plastic substrates.



Cleanup: Clean spray equipment as soon as possible with Thinner

SAFETY AND HANDLING

For safety precautions, please refer to Material Safety Data sheet and wear personal protective equipment when using this product.

The technical information contained in this Technical Data Sheet is to be understood as advice only and not binding in any respect.

All details about working with our products should be adapted to prevailing local conditions and materials used.