

TECHNICAL DATASHEET

FLEX AGENT

PRODUCT DESCRIPTION

It is a special additive used as a plasticizer for Basecoat and 2K systems.

PRODUCT BENEFITS

- 1- Improves flexibility of paints.
- 2- Provides protection for plastic and leather substrates
- 3- Prevents damage of material.
- 4- Inhibits toughness and cracking of plastic and leather parts
- 5- Excellent smooth finish.

RECOMMENDED USES

It is used on plastic and leather parts such as dashboards, leather seats and interior car accessories.



SURFACE PREPARATION

All surfaces must be clean, dry and free from dirt, oil and grease.




TECHNICAL CHARACTERISTICS

Color: Clear


Density: 0.9 g/cm³

Solids content: 30-40%



Mixing Ratio: The amount of FLEX to be added to the 2K products is around 10% of the net weight; however, the quantity varies and depends on the flexibility of the plastic to be painted.

Application: Mix the additive with the product as mentioned above. Adjust the spraying viscosity then apply with a spray gun.



Spraying Viscosity: 20 to 25 seconds ISO 4 cups @ 20°C



Cleanup: Clean spray equipment as soon as possible with thinner.

Storage: Store in a cool place. Guaranteed shelf life of 24 months in unused original containers

The technical information contained in this Technical Data Sheet is to be understood as advice only and not binding in any respect.

All details about working with our products should be adapted to prevailing local conditions and materials used.