

## **TECHNICAL DATASHEET**

# **READY PUTTY Step 1 – LOW VOC**

### **PRODUCT DESCRIPTION**

Ready to use low VOC filler for interior applications. Suitable for the smoothing of uneven rough surfaces as well as filling pores, cracks and surface imperfections. Also used to conceal the joints, texture surfaces such as old plaster, masonry or gypsum wallboard.

### **ENVIRONMENTAL STANDARDS & VOC REQUIREMENTS**

This paint conforms to environmental standards, is free of toxic materials, solvents and has a VOC content value <1% complying with **ASTM D2369-20**

### **PRODUCT BENEFITS**

- 1- Non-toxic, odorless product.
- 2- Easy to apply
- 3- Easy sanding
- 4- Great adhesion, durability.
- 5- High resistance to cracking.
- 6- Fast drying.
- 7- Elasticity and low shrinkage

### **RECOMMENDED USES**

All interior walls and ceilings such as concrete, masonry, brick, gypsum boards, non-chalking old paints, etc.

### **SURFACE PREPARATION:**

Prepare the substrate as mentioned below

- a) Rigid Surfaces should be cleaned and free from all traces of oil and laitance.
- b) Alkaline and acid surfaces should be cleaned and neutralized.
- c) Surfaces with previous coatings, blistered or chalking paints should be cleaned with scrapers and roughened with sand paper.

## PHYSICAL AND CHEMICAL PROPERTIES

### Physical Properties

Physical State Paste

Color White

Temperature 25°C

Relative Humidity 60%

Specific Gravity, ISO 2811 1.71 ± 0.05g/cm<sup>3</sup>

Viscosity, ISO 2884 270-280 poises

Drying Time, ASTM D5894 2-4 Hours per coat

Wet Film Thickness, ISO 2808 up to 1.5 mm

Recoat Time overnight

Coverage 12-15 m<sup>2</sup> per US gallon

Sag Resistance, ASTM D3730 Excellent

Leveling, ASTM D2801 Excellent

### Chemical Properties

% Solids by Weight 75 ± 2 %

% Solids by Volume 47 ± 2%

Very low VOC <1%

## APPLICATION

Prime the substrate as mentioned below:

- a) Apply primer for unpainted surfaces.
- b) Apply undercoat for chalking surfaces.

The condition of the surface affects the thickness of putty film. In normal applications thickness can reach 1.5 mm.

Clean tools and equipment with water immediately after use.

This product can also be diluted and rolled to achieve a textured pattern or decorative finish.

## **PACKING**

In cylindrical containers of the following capacities:

- 1 US gallon = 3.78 L.
- 1 US quart = 0.94 L.
- 1 Pail (5 U.S.G.) = 20L

## **STORAGE**

Avoid frost & excessive heat.

The technical information contained in this Technical Data Sheet is to be understood as advice only and not binding in any respect.  
All details about working with our products should be adapted to prevailing local conditions and materials used.