

## TECHNICAL DATASHEET

# Emulsified Bitumen

### PRODUCT DESCRIPTION

A stable bitumen emulsion rubber based which dries to give a flexible, jointless, black waterproof coating.

### PRODUCT BENEFITS

- 1- Fast drying
- 2- Excellent adhesion on concrete
- 3- Chemical resistance
- 4- Water resistance
- 5- Excellent Waterproofing properties

### RECOMMENDED USES

Brushable consistency for asphalt, concrete, corrugated iron, lead and zinc, roofing felt and other similar roof surfaces. It may be applied to both damp and dry surfaces. Ideal sealer before application of Tennis court system (Basecoat + Topcoat)

### SURFACE PREPARATION

The surface must be free from moss, lichen, dust, rust, grease, and any other foreign matter which can affect adhesion.

### PHYSICAL AND CHEMICAL PROPERTIES

Physical State	Liquid
Drying Time	3-4 hours
Spreading rate	Approx. 1.5-2 m <sup>2</sup> /Liter per coat depending on the porosity of the surface.

### APPLICATION

As a primer/sealer, this bitumen emulsion can be applied in one or two coats with a dilution of 30% to 60% with water.

Every coat must be allowed to completely dry before proceeding.  
It is advantageous to dampen brushes and brooms with water before and during use to avoid clogging and ensure maximum ease of application.

### **PACKING**

US Gallons and pails.

### **STORAGE**

Avoid frost & excessive heat.

The technical information contained in this Technical Data Sheet is to be understood as advice only and not binding in any respect.  
All details about working with our products should be adapted to prevailing local conditions and materials used.